

4.13 ROLLCAGES

- NOTE: Vehicles with a performance of 6.499 seconds (1/4 mile) / 4.139 seconds (1/8 mile), or quicker, must meet Top Doorslammer regulations or SFI 25.1D as a minimum.
- NOTE: All vehicles with a performance of 7.999 seconds (1/4 mile)
 / 5.094 seconds (1/8 mile), or quicker, are recommended to be built to the applicable SFI Chassis Specification.
- NOTE: Vehicles built to a SFI Chassis Specification are not required to adhere to the ANDRA Rollcage Specifications.
- NOTE: Vehicles built to a SFI Chassis Specification will not comply with Class Regulations for Modified Sedan and Modified Production due to additional floor bracing required for SFI compliance.
- NOTE: Rollcages built to Motorsport Australia Schedule J are not required to adhere to the ANDRA Rollcage Specifications.
- For Unmodified Modern Cars, Unmodified Cars and Modified Cars, see Definitions.

4.13.1 ROLLCAGE FABRICATION

Refer to either the ANDRA Removable Rollcage Specification or the ANDRA Welded Rollcage Specification for the current rollcage fabrication requirements.

No new rollcages will be permitted to be built using Electrically Resistance Welded (ERW) pipe or tube. Any vehicles / rollcages under fabrication prior to 31st December 2012 may apply to ANDRA Technical for special exemption to this rule.

4.13.2 VEHICLES BUILT PRIOR TO 2014

Vehicles and non-removable / welded rollcages fabricated prior to 1st January 2014 will be accepted for competition providing they meet compliance with requirements as detailed in 2013 ANDRA rulebook, unless other special exemption has previously been provided in writing.

4.13.3 REMOVABLE ROLLCAGES FABRICATED PRIOR TO 2014

Any vehicle with a pre-existing removable rollcage will be accepted according to the requirements as listed in the 2014 ANDRA rulebook, unless other special exemption has previously been provided in writing.

4.13.4 REMOVABLE ROLLCAGES FABRICATED AFTER 2014

Removable rollcages built after 1st January 2014 must comply with the ANDRA Removable Rollcage Specification in effect at the time of fabrication, or any later ANDRA Rollcage Specification.